



www.jkcementuae.com

BS EN 197-1 CEM I / 52.5 N

At JK White Cement we continuously strive for development of products with highest quality and perfection through our pioneering research and development, which far exceed the customer expectations.

We trust in the principal of product driven by the market needs. Thus, resulting in products which are developed that best suit the applications and requirements by constant innovation and research.



Description of JK White Cement - BS EN 197-1 CEM I / 52.5 N

"We shape our buildings, thereafter they shape us - by Winston Churchill"

JK White Cement in its basket of leadership products has provided the construction industry with a product which is designated under British Standards as EN 197-1 CEM I / 52.5 N. Our CEM I is highly accepted and used world-wide in numerous applications such as GFRC, Pre-cast panels, Aesthetic concrete, Mosaic Tiles, Masonry usage, Decorative products, etc.

Applications of JK White Cement CEM I 52.5 N

- Architectural & Decorative Concrete:- Coloured concrete cast in moulds/forms, Fountains, Border Stones Railing, Entrance Pillar, Cast Stone
- Glass Fiber Reinforced Concrete
- Pre-cast panels for exterior facade
- Designer Flooring:- Paving stones, Garden walkways, Pavement, Mosaic Tiles
- Masonry Application:- Plasters, Pointing Mortar, Tile Adhesive and Tile Grouts



Packaging available

- 25 Kg Paper and PP bag
- 40 Kg Paper and PP bag
- 50 Kg Paper and PP bag
- Jumbo packaging from 0.5 MT to 1.5 MT
- Loose Cement (Bulker)



Key attributes of JK White Cement CEM I 52.5 N

- High early strength
- It has min. whiteness of 90%
- It is produced from the raw material with highest purity
- Prolonged durability
- High reflectance

Benefits of using JK White Cement CEM I 52.5 N

- Superior quality and high durability
- Production of White coloured concrete (with suitable colour pigments), plaster or mortar
- Resulting in saturated colour & fine surface textures
- High strength and an unlimited formability
- Decorative harmony and universal use



Safety Precaution

Warning - Keep out of reach of children, avoid contact with eyes, skin and respiratory. Wear appropriate personal protection equipment like safety gloves, goggles, protection clothing and respiratory protection mask.

First aid -

Eyes contact: Rinse eyes thoroughly with water for at least 15 minutes, including under lids to remove all particles. Seek medical attention for abrasions and burns.

Skin contact : Wash with cool water and apH neutral soap or a mild skin detergent. Seek medical attention for rash, burns, irritation, dermatitis and prolonged unprotected exposures to wet cement, cement mixtures or liquids from wet cement.

Inhalation : Move person to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.

Ingestion : Do not induce vomiting. If conscious, have person drink plenty of water, medical attention, seek or contact poison control centers immediately.

Technical Support

Further information and advice on this product and the full range of JK White Cement products can be obtained through putting your comments over sales.fuj@jkcement.com

Note

The aforesaid information is based on our present state of knowledge and shall inform about our products and their application possibilities. Value and characteristics provided are typical and approximate size. It should not therefore be construed as guaranteeing specific properties of the product described or their suitability for a particular application. Subject to change without prior notice.

www.jkcementuae.com



JK Cement Works (Fujairah) FZC

Marketing office:

The Citadel Tower, Office No. 2007-2008,
Business Bay, Dubai (UAE)
P.O. Box 123630

Tel: **+971 4 2797303**, Fax: **+971 4 4203906**
sales.fuj@jkcement.com

Factory Address:

Plot No. 7, Block - K, Habhab - Tawian,
Fujairah (UAE) P.O. Box 5325

